

機械構造用合金鋼 (クロムモリブデン鋼)

在庫品● 取次ぎ品○

ミガキ丸鋼は他のページに記載されています。
参照 → P.11~P.12



(丸)

鋼種 径	SCM 415	SCM 420	SCM 435	SCM 440	調質鋼 SCM440M (M材, QT材)
13	●		●	●	
16	●	●	●	●	
19	●	●	●	●	
22	●	●	●	●	
25	●	●	●	●	●
28	●	●	●	●	●
30	○	○	○	○	
32	●	●	●	●	●
34	●	●	●	●	●
36	●	●	●	●	●
38	●	●	●	●	●
40	○	○	○	○	
42	●	●	●	●	●
44	●	●	●	●	●
46	●	●	●	●	●
48	●	●	●	●	●
50	●	●	●	●	●
55	●	●	●	●	●
60	●	●	●	●	●
65	●	●	●	●	●
70	●	●	●	●	●
75	●	●	●	●	●
80	●	●	●	●	●
85	●	●	●	●	●
90	●	●	●	●	●
95	●	●	●	●	●
100	●	●	●	●	●
110	●	●	●	●	●
120	●	●	●	●	●
130	●	●	●	●	●
140	●	●	●	●	●
150	●	●	●	●	●
160	●	●	●	●	●
170	●	●	●	●	●
180	●	●	●	●	●
190	●	●	●	●	●
200	●	●	●	●	●
210	○	○	○	○	
220	○	○	○	○	

在庫品でも欠品の場合がございます。その折は何卒御容赦願います。
定尺は標準で6,000Lですが、メーカーや径により変わる事があります。
SCM440M（調質鋼）の硬度は、HRC30±3です。

鉄鋼

ステンレス・チタン

アルミ

伸銅

樹脂

参考資料

(丸)

鋼種 径	SCM 415	SCM 420	SCM 435	SCM 440	調質鋼 SCM440M (M材, QT材)
230	○	○	○	○	
240	○	○	○	○	
250	○	○	○	○	
260	○	○	○	○	
270	○	○	○	○	
280	○	○	○	○	
290	○	○	○	○	
300	○	○	○	○	
310	○	○	○	○	
320	○	○	○	○	
330	○	○	○	○	
340	○	○	○	○	
350	○	○	○	○	
360		○	○	○	
370		○	○	○	
380		○	○	○	
390		○	○	○	
400		○	○	○	
410		○	○	○	
420		○	○	○	
430		○	○	○	
440		○	○	○	
450		○	○	○	
460			○	○	
470				○	
480				○	
500				○	
510				○	
520				○	
530				○	
540				○	
550				○	
560				○	
570				○	
600				○	
620				○	
650				○	

在庫品でも欠品の場合がございます。その折は何卒御容赦願います。
定尺は標準で6,000Lですが、メーカーや径により変わる事があります。
SCM440M (調質鋼) の硬度は、HRC30±3です。

鉄鋼

ステンレス・チタン

アルミ

伸銅

樹脂

参考資料