


SS アイビーム

取次ぎ品



kg/本

アイビーム

サイズmm A×B	厚さ		5.5	6.0	7.0	8.0
	t 1	t 2				
100× 75	5	8	71.0	77.4	90.3	103
125× 75	5.5	9.5	88.6	96.6	113	129
150× 75	5.5	9.5	94.0	103	120	137
150×125	8.5	14	199	217	253	290
180×100	6	10	130	142	165	189
200×100	7	10	143	156	182	208
200×150	9	16	277	302	353	403
250×125	7.5	12.5	211	230	268	306
	10	19	305	333	388	444
300×150	8	13	266	290	338	386
	10	18.5	360	393	458	524
	11.5	22	422	461	538	614
350×150	9	15	322	351	410	468
	12	24	480	523	610	698
400×150	10	18	396	432	504	576
	12.5	25	527	575	671	766
450×175	11	20	504	550	642	734
	13	26	632	690	805	920
600×190	13	25	732	798	931	1,064
	16	35	968	1,056	1,232	1,408

サイズmm A×B	厚さ		9.0	10.0	11.0	12.0
	t 1	t 2				
100× 75	5	8	116	129	142	155
125× 75	5.5	9.5	145	161	177	193
150× 75	5.5	9.5	154	171	188	205
150×125	8.5	14	326	362	398	434
180×100	6	10	212	236	260	283
200×100	7	10	234	260	286	312
200×150	9	16	454	504	554	605
250×125	7.5	12.5	345	383	421	460
	10	19	500	555	610	666
300×150	8	13	435	483	531	580
	10	18.5	590	655	720	786
	11.5	22	691	768	845	922
350×150	9	15	526	585	644	702
	12	24	785	872	959	1,046
400×150	10	18	648	720	792	864
	12.5	25	862	958	1,054	1,150
450×175	11	20	825	917	1,009	1,100
	13	26	1,035	1,150	1,265	1,380
600×190	13	25	1,197	1,330	1,463	1,596
	16	35	1,584	1,760	1,936	2,112

鉄鋼

ステンレス・チタン

アルミ

伸銅

樹脂

参考資料