

プラスチック金型用鋼 NAK55 (大同)

取次ぎ品○

プリハードン鋼 HRC40 程度



(平)

巾 厚さ	105	130	155	185	205	255	305	355	405	455	505	610	710
10			○		○								
13					○	○	(310)						
16					○		○						
19					○	○	○	○	○	○			
22			○		○	○	○	○	○	(23)	(23)		
27			○		○	○	○	○	○			25×605	
28										○	○		
32	○		○		○	○	○	○	○				
33										○	○	33×615	
38					○	○	○	○	○	○	○		
43			○		○	○	○	○	○	○	○		
53	○		○		○	○	○		○	(460)	○	53×605	
63		○	○	○	○	○	○	○	○		○		
73		○	○		○	○	○	○	○		○		
83					○	○	○	○	○	○		○	
93					○	○	○	○	○				
95									○				
105						(103)	(103)		○			○	
115						○	○		○		○		
125							○		○				
135							○		○		○		
145							○		○		○		
155									○				165×710
185													○
205													○
225											○		
235													○
255													○
285													○

鉄鋼

ステンレス・チタン

アルミ

伸銅

樹脂

参考資料

プラスチック金型用鋼 NAK80 (大同)

取次ぎ品○

プリハードン鋼 HRC40 程度

(平)

巾 厚さ	105	130	155	185	205	255	305	355	405	460	505	555	610	710	810
10	(106) ○		○		○		○		(410) ○						
13	(106) ○		○		○		(310) ○		○						
16	○		○		○	○	○								
19	○	○	○		○	○	○								
22	○	○	○	○	○	○	○	○	○	23×455 ○					
27	○	○	○	○	○	○	○	○	○						
32	○		○	○	○	○	○	○		33×460 ○	33×505 ○	33×555 ○			
38	○	○	○	○	○	○	○	○	○	○	○				
43	○	○	○		○	○	○	○	○	○					
50	○		○		○	○									
53	○	○	○	○	○	○	○	○	○	(455) ○	○				
63	○	○	○	○	○	○	○	○	○						
73	○	○	○	○	○	○	○	○	○		○				
83	○	○	○	○	○	○	○	○	○						
93			○		○	○	○	○							
103					○	○	○		(105t) ○						
115						○	○	○	○						
125						○	○	○	○						
135						○	○	○	○						
145							○	○	○		○				
155							○	○	○		○			○	
165								○	○				○	○	
185														○	
205														○	
235														○	
255														○	
285														○	
315															○

鉄鋼

ステンレス・チタン

アルミ

伸銅

樹脂

参考資料